

INORGANIC COMPOUND SACCHARIDE COMPOSITION, VEHICLE, RAPIDLY DISINTEGRATING COMPRESSION MOLDED PRODUCT, AND THEIR PRODUCTION

Patent Number: JP2000086537
Publication date: 2000-03-28
Inventor(s): YOKOI SHINICHIRO; SHISHIDO TAKESHI; TANAKA NOBUKAZU; HOTTA YOSHIHARU; CHO KIYOAKI; IKUSHIMA HEIJI
Applicant(s): FUJI CHEM IND CO LTD
Requested Patent: JP2000086537
Application Number: JP19980258946 19980911
Priority Number (s):
IPC Classification: A61K47/36
EC Classification:
Equivalents:

Abstract

PROBLEM TO BE SOLVED: To obtain, by spray drying a homogeneous suspension of an inorganic compound and a saccharide, an inorganic compound saccharide composition which has high fluidity and compression moldability in powder, rapidly disintegrating and/or dissolving properties when added into mouse or water in granule or tablet, and strength which does not allow disintegration during production and circulation.

SOLUTION: This composition is obtained by spray drying a homogeneous suspension of (A) an inorganic compound (preferably, magnesium methasilicate aluminate, synthetic hydrotalcite, dry aluminum hydroxide gel, precipitated calcium carbonate, magnesium silicate aluminate, magnesium silicate, or the like) and (B) a saccharide (preferably, erythritol, mannitol, sorbitol, xylitol, or the like). It is preferable that the composition contains components A and B at 0.5-99.5 wt.% and 0.5-99.5 wt.%, respectively. It is preferable that the particle size of the composition is 500 μ m or smaller.

Data supplied from the esp@cenet database - 12